



SUPER 1300 S

Turf sweeper for efficient collection of mowed material, leaves and other debris on sports, decorative, and utility turf.

- Perfect manoeuvrability
- Optimal sweeping result
- Overhead high dumping

SUPER 1300 S

The SUPER 1300 S is the ideal solution for efficiently collecting mowed material, leaves, and other debris on sports, decorative and utility turf.

It is equipped with a double sweeping roller system. Each sweeping roller has 4 sweeping rails. This ensures a perfect sweeping result, which guarantees residue-free cleaning of the turf and continuous and complete filling of the collection container.

The machine is mounted on the tractor in the draft links of the three-point hitch and is therefore extremely manoeuvrable. This is a significant advantage when working around trees and other obstacles.

- Hydraulic overhead high dumping for easy emptying up to 170 cm.
- Optional collision guard with integrated lighting system protects the SUPER 1300 S during backward manoeuvres.
- Optional level indicator works on the light-barrier principle and indicates when the container is approx. 90 % full.

The advantages:




Hydraulic overhead high dumping
or easy emptying up to 170 cm



Optional collision guard
with protected lighting unit



Level indicator
works on the light-barrier principle and indicates when the container is approx. 90 % full



Double sweeping roller system
for completely filling the container



Tracking accuracy
for driving close to the edge of obstacles

TECHNICAL DATA			
Working width in cm, approx.:	130	Drive via PTO shaft:	540 U/min
Container volume in m ³ , approx.:	1,6	Speed of the sweeping roller:	860 U/min
Overhead high dumping height in cm:	170	Minimum operating pressure of the hydraulic system:	140 bar
Approximate weight in kg (ready for use and empty):	650	Wheels (rear):	23x10.50 6PR
Permissible total weight in kg:	1050	Support wheels (depth control of sweeping head):	11x4.00-5 2PR
Dimensions L/W/H in cm: (including hitch)	280/170/167	Minimum power requirement of the tractor:	11 kW (15 PS)
Hydraulic requirements:	1x double-acting hydraulic connection with floating position		

Descriptions and illustrations are not binding. Changes in design and execution reserved.

Further Information:

Wiedenmann GmbH
Am Bahnhof | 89192 Rammingen | GERMANY
Fon +49 7345 953-0 | Fax +49 7345 953-233
info@wiedenmann.com

www.wiedenmann.com

