

TECHNICAL DATA	TERRA SPIKE® GXi 6 HD	TERRA SPIKE® GXi 8 HD
Working width in mm:	1400	1800
Weight (Standard design without tool and universal-joint shaft) in kg approx.:	590	900
Max. working depth in mm:	250	250
Dimensions L / W / H in mm approx.:	1150 / 1850 / 1350	1150 / 2270 / 1350
Mounting:	rear 3-point cat. I	rear 3-point cat. I
Tractor PTO speed:	540 RPM	540 RPM
QuickSet / QuickFit / PowerPack / VibraStop:	standard	standard
Max. admissible tractor engine power in kW/HP:	37 / 50	45 / 60
Minimum tractor lifting capacity in kg approx.:	800	1050
Solid tines Ø in mm:	5, 8, 12, 20	5, 8, 12, 20
Hollow tines Ø in mm:	10, 12, 16, 20, 25	10, 12, 16, 20, 25
Rear roller one piece in floating suspension:	optional	standard
Rear roller 3 parts in floating suspension:	optional	–
Turf retainer:	optional	optional
Addtl. weight:	optional	optional
Swathboard:	optional	optional
Nail board for 5 mm solid tines:	optional	optional
<b>Area coverage in continuous operation in square meters per hour at a crankshaft speed of 485 RPM</b>		
485 RPM; at 1,6 km/h; square hole spacing 55 mm approx.:	2200 m²/h	2800 m²/h
485 RPM; at 3,2 km/h; square hole spacing 110 mm approx.:	4350 m²/h	5600 m²/h
<b>Area coverage in continuous operation in square meters per hour at a crankshaft speed of 385 RPM</b>		
385 RPM; at 1,3 km/h; square hole spacing 55 mm approx.:	1800 m²/h	2288 m²/h
385 RPM; at 2,5 km/h; square hole spacing 110 mm approx.:	3350 m²/h	4400 m²/h

Descriptions and images are not binding. Construction and design are subject to modifications.

Further Information:

Wiedemann GmbH  
 Am Bahnhof | 89192 Rammingen | GERMANY  
 Phone +49 7345 953-0 | Fax +49 7345 953-233  
 info@wiedemann.com

[www.wiedemann.com](http://www.wiedemann.com)



18-212.03/18 www.mtk-ulm.de



## TERRA SPIKE® GXi 6 / 8 HD

Deep aeration and removal of compaction for a depth of 25 cm

- Central tine adjustment a depth adjustment
- Intergrated absorbing and tine mounting system
- Complete line of tools

We love turf. [www.wiedemann.com](http://www.wiedemann.com)

## For deep aeration and removal of compaction for a depth of 25 cm

The principle of "time is money" applies now more than ever to professional turf maintenance. Whether it's golf courses or sports grounds you're maintaining, the amount of time you have at your disposal is becoming increasingly limited while the players are placing ever more exacting demands on the quality of the turf. Regular deep spiking and deep aeration are important prerequisites for a healthy growth of roots. After decompacting the ground, the roots can penetrate deeper into the soil and thus make better use of water and nutrients. This improves water flow and the air budget of the soil, eliminates thatching and enhances the shear strength of the grass.

However, despite all the technical innovations in the past, this type of maintenance work has always been a timeconsuming task. Wiedenmann revolutionizes turf maintenance and set new standards in speed, productivity and quality of work. Save up to 60 % of the time you previously spent on maintenance.

However, your well-being is just as important to us as your productivity. That's why we have fitted two unique damping systems, VibraStop and PowerPack, into the TERRA SPIKE® GXi 6 / GXi 8 HD so you finish your work quickly and with a minimum of stress for you and your tractor. The drive concept

TwinDrive can be configured for various transmission ratios. Simply match the crankshaft speed to the power output of your tractor.

Don't waste valuable time setting the working depth or the loosening angle. You can make these adjustments quickly and without tools using the exclusive QuickSet System. The wide tine entry angle adjustment range of 90° to 65° allows loosening intensity to be adjusted optimally to the soil conditions and the degree of compaction of the soil. With the exclusive QuickFit System, tricky and timeconsuming tine replacement is now a thing of the past.

The TERRA SPIKE® GXi 6 / GXi 8 HD is very low maintenance with only 4 greasing points. The high productivity of the TERRA SPIKE® GXi 6 / GXi 8 HD will have you impressed. Loosen and aerate your turf at an unprecedented working depth and speed.


## Benefits:



### Precise tine penetration

ATC (Advanced Tine Control) controls the precise incision of the tines and ensures uniform hole spacing, even at high working speeds.

All movable parts of the ATC tines control are assembled completely outside the working and dirt area of the tines.



### Fast tine exchange

The tine mount is conically formed for TERRA SPIKE®, giving the tines an absolutely firm seat. The full or hollow tines are assembled or disassembled rapidly and effortlessly by the QuickFit integrated tine attachment and extraction system.



### Protection against damage

VibraStop/PowerPack form an efficient damping system against jolting and vibration. Together, they absorb perfectly jolts and vibrations caused by extreme compaction or stones. The result is unrivalled smoothness of running with a minimum of strain on the driver, tractor, deep aerifier and tools.



### Tool-free adjustment

Thanks to QuickSet, work depth of all TERRA SPIKE® models can be adjusted tool-free with three cranks and a few manual operations. The broad range of adjustment of the loosening angle from 90° – 65° lets you optimally adapt the loosening intensity to specific ground conditions and degree of compaction.

## Mode of operation:



### Tine holders

The highly robust tine holders with large-sized ball bearings are designed to withstand heavy-duty use. The ball bearings and tine holders are resistant to impact, dirt and sand and ensure reliable operation at all times.



### TwinDrive

TwinDrive transmits force symmetrically from both sides into the robust continuous crankshaft. If damaging peak stresses occur during operation, e.g. when the tines strike a stone, they are absorbed by the special ribbed vee belts on either side.



### Productivity

The less time is required for necessary deep loosening and aeration, the longer the turf can be used for sporting activities. The TERRA SPIKE® GXi 6 / GXi 8 HD is designed for high working speeds and excellent quality of work. Your players will thank you.



### Crankshaft

The robust, computer-optimized crankshaft runs in large maintenance-free ball bearings. You will be surprised by how smoothly the TERRA SPIKE® GXi 6 / GXi 8 HD runs.



### Turf retainer

The optional turf retainer prevents damage to shallow rooted turfs. The turf retainer is designed to match the tine spacings, regardless of whether you fit 2 or 4 tines per tine holder.

## Optional equipment:



### Multi-tine holder

Solid tines 5 x 65, 5 x 135, 8 x 65 or 8 x 150 mm are mounted in the multi-tine holder "nail board". 24, 16 or 8 tines can be mounted, depending on the task and the required hole pattern. The "sandwich construction" of the nail board allows quick and easy tine replacement.



### Optional ballast weight

For heavy duty conditions of use, the weight of the GXi range can be increased by adding an optional ballast weight of approx. 45 kg.



### Range of tines

A complete range of solid tines with diameters 5, 8, 12, 20 mm, as well as hollow tines with diameters of 10, 12, 16, 20 and 25 mm let the TERRA SPIKE® GXi 6 / GXi 8 HD master every job.



### Swathboard

When using hollow spoons you can place the cores in the swath in a single operation with the optional swath board. This makes subsequent collection of the cores much easier. The swath board is very robust and easy to attach.



### Rear roller

The optional rear roller of the GXi 6 is single or three-parted and mounted in a floating suspension which allows the roller to follow the ground contours precisely.